

EcoTestr™ pH 2

Simplicity with Oakton reliability

Simple single-line display – Large upright display is easy to read

±0.1% pH full-scale accuracy – Suitable for many applications

Transparent protective cap – Doubles up as a container for sensor conditioning or on-site calibration

Waterproof, dustproof housing – Meets IP67 rating, plus it floats!

Long-lasting sensor with PVDF reference junction – Large volume of polymer gel reference gives long, clog-free, sensor lifespan

Click-lock battery compartment – Simply lift and remove cover to replace batteries; no additional tools required

Push-button calibration – Calibrate more precisely than trimpot adjustment; no screwdrivers necessary

Automatic temperature compensation (ATC) – Gives you accurate readings even with fluctuating temperatures

Hold function – Freezes reading until you can record it

Auto shutoff – Extends the life of the batteries



35423-10
EcoTestr pH 2



Transparent protective cap keeps sensor moist when stored upright.



Convenient pocket/belt clip



Convenient, soft vinyl, belt-loop carrying case 35624-45 keeps tester handy.



Hydroponics



Education



Swimming Pools

ISO9001:2000
CERTIFIED SUPPLIER



1 year
warranty
meter only

Specifications

Model	EcoTestr pH 2
Range	0.0 to 14.0 pH
Resolution	0.1 pH
Accuracy	±0.1 pH
Calibration	Three-point, automatic (4.0, 7.0, or 10.0)

Temperature compensation: automatic (ATC), from 0 to 50°C (32 to 122°F)
Operating temperature: 0 to 50°C (32 to 122°F)
Power: four 1.5 V alkaline batteries (included), 250 hrs continuous use: Eveready® A76 or LR44 equivalent replacement

Dimensions
Unit only: 1¼" x 1½" x 6½" (3.2 x 3.8 x 16.8 cm)
Boxed: 1½" x 5¼" x 9¾" (3.8 x 13.6 x 24.8 cm)
Weight
Unit only: 3.25 oz (90 g); **Boxed:** 6 oz (170 g)

Ordering Information

Catalog number	Description	Included
WD-35423-10	EcoTestr pH 2	Tester, integral sensor, and batteries

Accessories

WD-35624-45 Belt-loop waterproof carrying case; holds one waterproof tester (order separately). Snap lock fastens case around your belt; hook-and-loop seal secures tester. Pictured above. 5½"L x 2"W x 7¾"H (14 x 5 x 20 cm).

WD-35624-70 Calibration kit includes calibration buffer pouches (two each of pH 4.01, 7.00, 10.00, and rinse water), sample jar, and hard carrying case. (Tester not included)

WD-09377-16 Replacement batteries, 1.5 V. Pack of 6